

**Multi-functional cable and fishing equipment with video system and
underwater image video system using the same**

Technical Field

5

The present invention relates to a multifunctional cable, and fishing equipment and underwater image video system using the same, and more particularly to a multifunctional cable which has both capability and durability due to several micro wires included, and fishing equipment and underwater image video system using the same.

10

Background Art

15

Recently, there have been many efforts to develop fishing equipment with underwater image photographing systems, which would enhance the experience by allowing the user to observe the underwater environment by way of the video system attached to the fishing equipment.

20

For example, the Korean Patent Publication of registration No. 1988-76867 discloses fishing equipment that enables the user to watch images sent from underwater video camera to an external display device through electric wire while staying out of water.

But in reality, this concept is still not on a practical level, thus things like fishing while observing the underwater conditions and environment hasn't come true yet.

25

That is because all underwater photographing and transmitting system including fishing equipment with image system require some kinds of channels that can send and receive signals. These channels are needed to send underwater image signals out of the water and receive these signals to display them on the display device. Of course, it is impossible to use the conventional fishing lines or general electric wires for this purpose.

In other words, to construct fishing equipment with underwater image photographing system, the cable has to be thin, durable, and flexible at the same time in order to send/receive various signals including image signals.

5 The present invention is designed to provide a multifunctional cable that has all the characteristics needed in a fishing line such as fineness, flexibility and durability, and also has the capability of sending/receiving of electricity and image signals as mentioned above. Another purpose of the present invention is to provide fishing equipment with video system and underwater image video system using the above mentioned multifunctional cable, which enables the user to photograph the underwater environment and fish
10 effectively.

Disclosure of Invention

The multifunctional cable that accomplishes the above mentioned purpose is
15 characterized that comprising:

electric cords, a image signal cord and one or more control cords to transfer signals of sounds, supersonic waves, temperature information or control orders with individual inner coats, and exterior of these cords are molded or filled with flexible and durable molding resin or fibers, and the outer surface of the cable is covered with an abrasion
20 resistant coat.

Said control cord is used to channel signals of sounds, temperature information, and control order, etc. and several may be included in a multifunctional cable according to the function needed. But it is also possible to manufacture multifunctional cable according to the present invention without control cords. This is because sometimes according to the
25 usage, it is possible to achieve the purpose by using multifunctional cables without control cords. For example, there are cases when the user only needs image signals.

On the other hand, all fishing equipments with video system and underwater image video systems according to the present invention are characterized that using above mentioned multifunctional cables according to the present invention.

5 The first embodiment of the fishing equipment with video system according to the present invention is characterized that comprising:

multifunctional cable according to the present invention;

10 a photographing part comprised of a weight connected to one end of the multifunctional cable, having a built-in camera and one or more control devices selected from supersonic wave sensor, digital temperature sensor, underwater mike, pressure sensor, vibrating motor, geomagnetic sensor and camera angle adjustor and several tying rings for the fishhook are formed; and a buoyancy regulating float connected to a point of said multifunctional cable;

15 an external device part connected to the other end of said multifunctional cable, and comprised of a display panel which receives and displays various signals including image signals from said photographing part through said multifunctional cable, a controller communicating to the control devices through the multifunctional cable and controls them by exchanging control signals through the multifunctional cable, and an electric power supplier which supplies power to the above photographing part, display panel and
20 controller.

The second embodiment of the fishing equipment with video system according to the present invention is characterized that comprising:

25 a photographing part comprised of a weight connected to one end of the multifunctional cable according to the present invention, having a built-in camera, one or more control devices selected from supersonic wave sensor, digital temperature sensor, underwater mike, pressure sensor, vibrating motor, geomagnetic sensor and camera angle

adjustor, several tying rings for the fishhook are formed, and a wireless radio sending/receiving float connected to said weight through said multifunctional cable and including a first radio sending/receiving circuit having an electric power supplier inside; and

5 an external device part comprised of a second radio sending/receiving circuit exchanging signals with the first radio sending/receiving circuit; a display panel connected to the second radio sending/receiving circuit, and receives and displays various signals including image signals received by the second radio sending/receiving circuit from said photographing part; a controller connected to the second radio sending/receiving circuit
10 and controls the control devices by exchanging control signals through the second radio sending/receiving circuit; and an electric power supplier which supplies power to the second radio sending/receiving circuit, display panel and controller.

The third embodiment of the fishing equipment with video system according to the
15 present invention is characterized that comprising:

multifunctional cable according to the present invention;

a photographing part comprised of a weight connected to one end of the multifunctional cable, having a built-in camera and one or more control devices selected from supersonic wave sensor, digital temperature sensor, underwater mike, pressure sensor,
20 vibrating motor, geomagnetic sensor and camera angle adjustor, several tying rings for the fishhook are formed; and a buoyancy regulating float connected to a point of said multifunctional cable;

a wireless transceiver connected to the other end of said multifunctional cable, having a first radio sending/receiving circuit with an electric power supplier inside and
25 fixable to a point outside the water; and

an external device part comprised of a second radio sending/receiving circuit exchanging signals with the first radio sending/receiving circuit; a display panel connected

to the second radio sending/receiving circuit, and receives and displays various signals including image signals received by the second radio sending/receiving circuit from said photographing part; a controller connected to the second radio sending/receiving circuit, and controls the control devices by exchanging control signals through the second radio sending/receiving circuit, and controls the display panel; and an electric power supplier which supplies power to the second radio sending/receiving circuit, display panel and controller.


And, it is possible to choose only a type of control device from the control devices such as - a built-in camera, supersonic wave sensor, digital temperature sensor, underwater mike, pressure sensor, vibrating motor, geomagnetic sensor or camera angle adjustor- and install it inside the weigh, but it is also possible to choose two or more devices and install them all.

With the fishing equipment with video system according to the present invention, the preferred shape of the weight case can be a bisected case or a lure shaped case. Said bisected case has a hinge on one side and a fixing flange on the other side of the case, thereby integrated and disintegrated using fixing bolts.

And whether the shape of the weight case is a lure shape or a bisected case shape, it is desirable that the bottom part of the weight is filled with materials of high density, the middle part has a built-in camera and control devices, and the upper part has a void, so that the weight always stand stably under the water.

It is also desirable to have a underwater float at a point of the multifunctional cable connecting the weight and the buoyancy regulating float or the wireless radio sending/receiving float, and one or more supplementing weight hung to the ring attached to the bottom of the weight case, thereby prevents the weight from fluctuating under the water and helps to regulate the density of the weight.

On the other hand, it is recommended to have a flexible tube or a thin wire on the weight, thereby make it possible to control the location of the fishhook and shooting angle of the camera.

Also, a preferred form of the camera angle adjustor of the fishing equipment with video system according to the present invention may be the  shaped fixtures, driven by a motor installed in the weight and installed so as to place each end of the fixture at each end of the weight case on the upper part of the weight, thereby the camera angle is adjustable to any angle by driving said fixture through controlling the rotating direction of the motor by using the controller of the external device part.

On the other hand, a point of the multifunctional cable between said weight of the photographing part and the float may be cut and a connector be installed to connect them, thereby the user can exchange the weight of the photographing part whenever needed.

On the other hand, the first embodiment of the underwater image video system according to the present invention is characterized that comprising:

multifunctional cable according to the present invention;

a photographing part comprised of a photographing device connected to one end of the multifunctional cable, having a built-in camera and one or more control device selected from supersonic wave sensor, digital temperature sensor, underwater mike, pressure sensor, geomagnetic sensor and camera angle adjustor inside; a diver's location indicating buoy connected to a point of said multifunctional cable; and a winding reel used to control the length of the multifunctional cable between the buoy and the photographing device according to the distance between the water surface and the diver;

an external device part connected to the other end of the above multifunctional cable and comprised of a display panel which receives and displays various signals including image signals from the photographing part through the multifunctional cable, a controller communicating with the control devices through the multifunctional cable and

controls the control devices by exchanging control signals through the multifunctional cable, and an electric power supplier which supplies power to the above photographing part, display panel and controller.

5 The other embodiment of the underwater image video system according to the present invention is characterized that comprising:

 a photographing part comprised of a photographing device connected to one end of the multifunctional cable according to the present invention, having a built-in camera and one or more control devices selected from supersonic wave sensor, digital temperature
10 sensor, underwater mike, pressure sensor, geomagnetic sensor and camera angle adjustor inside, a diver's location indicating buoy connected to the other end of the above multifunctional cable, having a first radio sending/receiving circuit inside, and a winding reel used to control the length of the multifunctional cable between the buoy and the photographing device according to the distance between the water surface and the diver;

15 an external device comprised of a second radio sending/receiving circuit exchanging signals with the first radio sending/receiving circuit; a display panel connected to the second radio sending/receiving circuit and receives and displays various signals including image signals received by the second radio sending/receiving circuit from the photographing part; a controller connected to the second radio sending/receiving circuit
20 and controls the control devices by exchanging control signals through the second radio sending/receiving; and an electric power supplier which supplies power to the second radio sending/receiving circuit, display panel and controller.

 Additionally, it is recommended to install a twin lens reflex on the exterior case of said photographing device, composed of a case of each end open and with at least one or
25 more curves, a hinge installed on the curved part of the above case, and a reflector installed on the curved part to reflect the incident ray to a set degree.

The camera angle adjustor of the underwater image video system may be the same as that of the above fishing equipment with video system according to the present invention, and if this kind of angle regulator is applied, it is possible for the diver to fix the photographing device on a point under the water, come out of the water, and watch the
5 underwater environment for a long time from out of the water.

Brief Description of Drawings

Fig 1 is a cross sectional view of the internal structure of the multifunctional cable
10 according to one preferred embodiment of the present invention;

Fig 2 shows the usage state of a whole composition of the fishing equipment with video system according to one preferred embodiment of the present invention;

Fig 3 is a cross sectional view that shows the detail composition of the weight of the photographing part of the fishing equipment with video system according to one preferred
15 embodiment of the present invention;

Fig 4 (a) and Fig 4 (b) are side cross sectional views that show the weight of the photographing part of the fishing equipment with video system according to some preferred embodiments of the present invention;

Fig 5 (a) and Fig 5 (b) are cross sectional views that show the whole composition of
20 the photographing part of the fishing equipment according to some preferred embodiments of the present invention;

Fig 6 (a) and Fig 6 (b) are structural views that show the various structures of the external device part of the fishing equipment with video system according to the present invention;

25 Fig 7 shows the usage state of a complete composition of the underwater image video system according to the present invention;

Fig 8 is a cross sectional view of the photographing device of the underwater image video system according to the present invention;

Figure 9 is a side cross sectional view of the twin lens reflex of the underwater image video system according to the present invention;

5 Figure 10 is a cross sectional view that shows the entire structure of the buoy of one preferred embodiment of the underwater image video system according to the present invention.

10 **Best Mode for Carrying Out the Invention**

Now, preferred embodiments of the present invention will be described in detail with reference to the annexed drawings.

Fig 1 is a cross sectional view of the internal structure of the multifunctional cable according to one preferred embodiment of the present invention. As shown in Fig 1, the multifunctional cable 10 according to the present invention has two strands of electric
15 cords 11 that channel electricity, a image signal cord 12 that channels image signals and a control cord 13 that channels control signals inside, all of which have inner coats 11c, 12d, 13d on their surfaces respectively, arranged in a stable manner; and the outside of above cords is molded with flexible and durable molding resin 14; and outer surface of the
20 molding resin is coated with an abrasion resistant exterior coat 15 again.

The image signal cord 12 and control cord 13 have inner lines 12a, 13a and outer lines 12b, 13b respectively; and insulating layers 12c, 13c are formed between them; The electric cords 11 also have the inner lines 11a and outer lines 11b, but do not have insulating layers between them 11a, 11b.

Also as shown in Fig 1, it is desirable to apply different diameters to the electric cords 11, and, image signal cord 12 and control cord 13 inside the cable 10, thereby prevent the cords 11, 12, 13 from getting twisted.

The multifunctional cable 10 needs to be light and durable like the fishing line and must be able to channel electricity and signals at the same time. So a recommended specification of multifunctional cable suitable for standard specifications of a high definition CCD DC 12V, 250mA may be as shown in Table 1.

【Table 1】

Item		Unit	Image Signal Cords / Control cords	electric cords
Number of cores		number	1 Each	2
Inner Lines	Material		Silver Plated Copper	Tin Plated Copper
	Diameter	mm	0.12	0.306
Insulating Layer	Material		Teflon	
	Diameter	mm	0.307	
Outer Lines	Material		Tin Plated Copper	Tin Plated Copper
	Thickness	mm	0.03	0.65
Inner coat	Material		Teflon	PE or PP
	Diameter	mm	0.46	
Molding Resin	Diameter	mm	0.92	
	Material		Kevlar or Carbon Resin	Kevlar or Carbon Resin
Exterior coat	Material		PE or PP	
	Diameter	mm	1.5	

According to Table 1, the recommended materials for the cords used in the multifunctional cable according to the present invention are; Tin plated copper for the electric cords 11, silver plated copper for the inner line 12a, 13a and tin plated copper for the outer line 12b, 13b of the image signal cord 12 and control cord 13 are used, and a Teflon insulating layer 12c, 13c is formed between said inner lines 12a, 13a and outer lines 12b, 13b.

The electric cord 11 formed as above uses polyethylene (PE) or polypropylene (PP), and the image signal cord 12 and control cord 13 use Teflon to form an inner coat and complement the insulation and hardness.

5 These electric cords 11, image signal cord 12 and control cord 13 are united using molding resin 14 or the voids between the cords 11, 12, 13 are filled with molding resin 14 having flexibility, excellent tensile properties and high durability like Kevlar fibers or carbon resin, then, the exterior coat 15 is formed using abrasion-resistant and flexible resin like polyethylene or polypropylene.

10 By using the structure and material composition mentioned above, it is possible to make the multifunctional cable 10 according to the present invention have a total cable diameter of 1.5mm, an electric cord 11 have a diameter of 0.306mm, an image signal cord 12 and control cord 13 have a diameter of 0.12mm, and still have the characteristics of a electric cord and flexibility and durability at the same time.

15 On the other hand, as stated above, the number and dimensions of the image signal cords and control cords mentioned above may be changed according to its use, and this kind of change is also regarded as belong to the scope of the present invention.

20 Now, a preferred embodiment of the fishing equipment with video system according to the present invention will be explained by referring to Figs 2 to 6 which show the structure of fishing equipment with video system according to this invention.

As shown in Fig 2 to Fig 6 (a), (b), the fishing equipment of this example is composed of a photographing part (200) comprising a weight 210 having a camera 220 and control device 213 inside, and a float 230, thereby photograph the underwater environment; an external device part 100 comprising display panels 110, controllers 120 and electric power suppliers 130, thereby display images taken by the photographing part 200 and control the control devices 213; and a multifunctional cable 10 that connects the
25 devices mentioned above.

As shown in Fig 4 (b), the multifunctional cable between the weight 210 and float 230 of the photographing part can be cut, and a connector 20a, 20b can be installed to connect two ends of the cut multifunctional cable. This make it easy for the user to change the weight 210 whenever needed.

5 Also, the weight 210 of the photographing part 200 may be made in various shapes. As shown in fig 4 (a) and (b), bisected case shape 211 and known lure shape case 211 may be desirable.

The bisected case shape 211 mentioned above has a hinge 211a on one part, a fixing flange 211b on the other part, and two parts of the case are combined together by using a
10 fixing bolt 211c. A Lure shape 211' means that the case of the weight has lure shape, and when this type of weight shape is adopted, the camera 212 should be placed in the back so that the attack of fishes cannot destroy the camera.


As shown in Fig 3, it is possible to outfit several tying rings 215 and fixing grooves 216 on the surface of the case 211, which help the tying of the fishing line 10 and fishhook
15 and installing of the lighting systems 220. And inside of the case, a camera 212 for underwater photographing and control devices 213 are built in.

One or several devices can be chosen and attached together selected from the group of built-in camera, supersonic wave sensor, digital temperature sensor, underwater mike, pressure sensor, vibrating motor, geomagnetic sensor and camera angle adjustor as the
20 control device 213. With these control devices 213, the user can check the temperature, pressure, depth, current and sound of the water and find a school of fish from outside of the water. And by using the camera angle adjustor, the user can control the angle of the camera and shot the underwater environment much more precisely.

Among the control devices mentioned above, the digital temperature sensor,
25 underwater mike, pressure sensor, vibrating motor, and geomagnetic sensor can be one of the known micro type devices; wherein sensing parts of the pressure sensor, temperature

sensor, and geomagnetic sensor should be exposed to the surface of the weight case because they need contact with water.

Especially as shown in Fig 4 (b), if a vibrating motor 213b is installed as a control device 213 to the lure shaped weight 211', the lure shaped weight 211' swims under the water according to the vibration of the vibrating motor 213b and this allures the carnivorous fishes because this lure formed weight 211' may seem like a real live fish to them.

Also, as shown in Fig 4 (a), the camera angle adjustor is built by installing the  shaped fixture 219 driven by a motor 218 installed inside the weight 210, as to place each end of the fixture at each end of the weight case on the upper part of the weight. So the camera angle is adjustable to any angle by the drive of the above mentioned fixture 219 by controlling the rotating direction of the motor 218 through the controller 120 of the external device part 100.

Also, in this invention, the case 211 of the weight 210 mentioned above has different density to prevent the current to shake the camera and to knock it off focus. In this example, the bottom part is filled with high-density material 214a, a camera 212 and control system 213 are built in the middle part, and an empty space 214b is formed in the upper part as shown in Fig 3. The difference of the density of each part makes the weight 210 always stand under the water.

And as shown in Figs 5 (a) and (b), It is possible to equip a underwater float between the weight 210 and buoyancy regulating float 230 connected by the multifunctional cable 10, thereby prevent the weight 210 from fluctuating, and to hang one or more supplementing weight 219 to the ring 218 attached to the bottom of the weight, thereby make it easy to regulate the density and the diving depth of the weight 210.

Lighting 220 provided for this weight 210 is composed of an illuminator 221a, 221b, batteries 222 and a switch 223 inside a sealed case 224 as shown in Fig 4. One or more

illuminators can be chosen and attached from the high luminance illuminating diode 221a or the infrared light 221b according to the use.

On the case 224 mentioned above, there are fixing holes 225 corresponding to the fixing grooves 216 formed on the weight 210's case 211, so that they can be connected
5 together with bolts.

The weight 210 and float 230 are connected together by the multifunctional cable 10 according to the present invention. And as shown in Fig 3 and Fig 4 (a), certain length of flexible tube 217b or thin wire 217a is installed, which allows the location of the camera angle and fishhook to be adjustable.

10 If the user bends the flexible tube 217b or thin wire 217a to a certain degree before putting the photographing part 200 under the water, the camera 212 in the weight 210 forms a fixed shooting angle under the water, and the fishhook also stays at a certain point under the water.

As shown in Fig 6 (a), the external device part 100 connected to the photographing
15 part 200 mentioned above, is composed of a display panel 110, controller 120 and electric power supplier 130, thereby displays images shot by the photographing part 200, operates the control devices, and supplies electric power to the devices. Wherein, the controller 120, display panel 110 and electric power supplier 130 may be integrated form or separate form. And, the external device part may be attached to the fishing pole and integrated
20 with it as shown in the present example, or made separately from the fishing pole as a separate equipment

As shown in Fig 6 (b), if these devices of external device part 100 are used separately from the fishing pole, the external device part 100 can be composed effectively with the known mobile phone with power supply unit, display unit, input unit, image
25 storage unit and control unit, by adding a connector to connect with the end of the multifunctional cable, or by installing a radio sending/receiving circuit 334 which

exchange signals such as image signal with the wireless radio sending/receiving float of the photographing part or the wireless transceiver inside, or by adding or installing both of the above mentioned means to be used optionally by the user. In this case, the underwater images sent to the mobile phone can be sent to other places via mobile Internet and so on.

5 And it is also possible for several people to watch underwater images from different spots by installing several external device parts 100.

And, the above mentioned electric power supplier 130 is composed of known adaptor and batteries, and the well-known technology related to the display technology can be applied to the construction and installation of external device part 100 especially power
10 supplier 130, so the detailed drawings and explanations are omitted in this specification.

The photographing part 200 and external device part 100 with the above mentioned constructions are connected with each other by different means according to the communication type. If the wireless radio communication system is adapted, the photographing part 200 and external device part 100 with radio sending/receiving circuits
15 231 having an electric power supplier, are connected with each other by normal fishing lines as shown in Fig 5 (a). But if the wire communication system is adapted, the photographing part 200 and external device part 100 without radio sending/receiving circuits 231, are connected with each other by multifunctional cables according to the present invention, thereby channel signals and electric power through them.

20 On the other hand, if a little modification is added to these devices, it is possible to compose a fishing equipment with wireless type video system by equipping an individual wireless transceiver 333 having a first radio sending/receiving circuit, and connecting it with buoyancy regulating float of the photographing part 200 similar to that of above mentioned wire type, and then attaching it to one spot out of the water, desirably to a spot
25 on the fishing pole, more desirably to a spot on the grip part of the fishing pole and making the other devices of the external device part 100 such as controller, display panel into portable type with a second radio sending/receiving circuit inside, so that said radio

sending/receiving circuits (the first and second radio sending/receiving circuit) communicate with each other.

Addition to the above mentioned construction, by forming an inlet hole 141 and an outlet hole 142 on the fishing pole at the starting point and extruding point of the cable
5 respectively, thereby make the multifunctional cable 10 pass through inside the fishing pole. By adapting this structure, it is possible to prevent the cable 10 getting tangled outside the fishing pole, and to make it easy to carry with.

Fig 7 shows the usage state view of a complete construction of the wireless type
10 underwater image video system according to a preferred embodiment of the present invention; and Fig 8 is a cross sectional view of the photographing device of the underwater image video system according to the present invention. Now, the desirable example of the underwater image video system according to the present invention will be described by referring to Figs 7 to 8

15 The underwater image video system according to the present example is composed of a photographing part 300 comprising a photographing device 310, winding reel 320, control devices 312 and a buoy 330 thereby take pictures of underwater environment, and an external device part 400 comprising display panels, controllers and an electric power suppliers thereby display images taken by the photographing part 300 and control the
20 control devices 312.

As shown in Fig 8, the photographing device 310 has fixing grooves 313 on the surface so as to install the lighting devices 314, and camera 311 for photographing underwater environment, control devices 314 such as supersonic wave sensor, digital temperature sensor, underwater mike, pressure sensor, geomagnetic sensor and camera
25 angle adjustor similar to the weight 210 of the above mentioned fishing equipment with video system.

Addition to the above structure, the photographing device 310 has a fixing clip 317 and a twin lens reflex 316 outside of the device 310 to carry out more effective photographing. The fixing clip 317 is for the easy attaching/detaching of the photographing device 310 to the diving apparatus, so that the diver moves freely under the water without any restriction due to the photographing device 310. And the twin lens reflex 316 helps the diver to keep focus easily and to adjust the frame with observing the image being taken by the camera under the water.

As shown in Fig 8, the twin lens reflex is composed of a case 316a, a hinge 316b to connect the cases and a reflector 316c. The case 316a has the shape of each end open to make it possible for the light to come in and out through the case, and has a curved part between the two ends. A hinge 316b is installed on the curved part for the case to be folded freely. And a reflector 316c is installed inside the case on the curved part, thereby the incident ray can be reflected and escape from the case to a certain degree. With the construction described above, the user can adjust the focus and frame of the camera 311 after observing the spot where the camera 311 is taking pictures through the twin lens reflex 316.

The photographing device 310 and the buoy 330 floated on the surface of water are connected with each other by the multifunctional cable 10 according to the present invention. Additionally, a winding reel 320 can be prepared between the photographing device 310 and the buoy 330 to make it easy for the diver to control the length of the multifunctional cable 10 according to the diving depth. To help the easy attaching/detaching of the winding reel 320 to the diving suit, it is desirable for the winding reel 320 to have a clip or so.

The external device part 400 connected to the photographing part 300 can be constructed similarly to that 100 of the fishing equipment with video system, and the functions of the devices are same for the most part, so the additional drawings and detailed explanations are omitted in this specification.

On the other hand, a kind of communicating path is necessary to exchange signals between the photographing part 300 and external device part 400. In this example, radio sending/receiving circuits are installed inside the buoy 330 and the external device part 400, which exchange information by wireless type.

5 Fig 10 shows the structure of a buoy 330 including radio sending/receiving circuit with electric power supplier 332 inside.

But, in the case that the photographing part 300 and external device part 400 are connected by a cable, there is no radio sending/receiving circuit in the buoy 330, and the electricity and signals are exchanged by using the multifunctional cable according to the
10 present invention.

Also, although we have explained the cases where radio sending/receiving circuits were built in, but when the diver simply sends image signals and other underwater signals to the external device part 400, even simple type such as radio transmitting circuit is installed in the buoy 330 and radio receiving circuit is installed in the external device part
15 400 will be sufficient. These kinds of structure are also considered to be in the scope of this invention.

If the wireless type is adapted for the communication, it is possible to use general radio frequency, but it is more desirable to construct a network of 2.4GHz radio circuit, and use several channels provided by the 2.3GHz radio circuit network mentioned above to
20 observe the underwater images taken by several divers at the same time.

Although we have explained about the example of wireless type underwater image video system with radio sending/receiving circuits, instead of using radio sending/receiving circuits mentioned above, it is possible to connect the buoy and the external device part 400 using the multifunctional cable according to the present invention
25 and exchange signals through this cable. In this type of system, the other components excepting the radio sending/receiving circuit explained with the wireless type underwater image video system can be applied unchanged.

Also, the display and control functions using mobile phones on the fishing equipment with video system can be applicable.

Only some examples on how to use the multifunctional cable, the fishing equipment with video system and underwater image video system are explained above. But this description is not everything, and all simple modifications made to the technology concerning this invention are in the range of this invention.

Industrial Applicability

The multifunctional cable according to the present invention may be useful in many types of underwater image shooting systems including fishing equipment with video system, because it is composed of micro cords with flexibility and durability and possible to transmit electricity, image signals and control signals needed in the display devices and control devices, thereby possible to prevent the problems of conventional type of cables such as easy cutting or easy detection by the fishes.

Also, it is possible not only to carry out fishing or long time underwater photographing more effectively by using the fishing equipment with video system or underwater image video system according to the present invention, but also to observe the movements of schools of fish, to check the temperature and depth of the water and to listen to underwater sounds to capture the fishes.

Since the underwater image video system mentioned above can be made with low cost, it is expected that it will replace the previous high costing products. And since someone out of the water can watch what is happening under the water, accidents under the water can be prevented, and the fear that divers might have about water can be alleviated.

Claims

1. A multifunctional cable comprising:

electric cords, a image signal cord and one or more control cords to transfer signals of sounds, supersonic waves, temperature information or control orders with individual inner coats; and

exterior of these cords are molded or filled with flexible and durable molding resin or fibers, and the outer surface of the cable is covered with an abrasion resistant coat.

2. The multifunctional cable according to claim 1 characterized that using tin plated copper line as the lines of the electric cords and polyethylene or polypropylene as the inner coat material of the electric cords; silver plated copper line as the inner line and tin plated copper line as the outer line of the image signal cord and control cord and Teflon as the inner coat material of the image signal cord and control cord; Kevlar fibers or carbon resin as the molding resin; and polyethylene or polypropylene as the abrasion-resist exterior coat material.

3. The multifunctional cable according to claim 1, wherein the diameter of the electric cords is different from the diameter of the image signal cord and control cord.

4. The multifunctional cable according to claim 3, wherein the diameter of electric cord is 0.306mm, the diameters of image signal cord and control cord are 0.12mm, and the diameter of the whole multifunctional cable is 1.5mm or below.

5. A multifunctional cable comprising:

electric cords and a image signal cord with individual inner coats; and

exterior of these cords are molded or filled with flexible and durable molding resin or fibers, and the outer surface of the cable is covered with an abrasion resistant coat.

6. The multifunctional cable according to claim 5 characterized that using tin plated copper line as the lines of the electric cords and polyethylene or polypropylene as the inner coat material of the electric cords; silver plated copper line as the inner line and tin plated copper line as the outer line of the image signal cord and Teflon as the inner coat material of the image signal cord; Kevlar fibers or carbon resin as the molding resin; and
5 polyethylene or polypropylene as the abrasion-resist exterior coat material.

7. A fishing equipment with video system comprising:

a multifunctional cable according to claim 1 through claim 6;

10 a photographing part composed of a weight connected to one end of said multifunctional cable, having a built-in camera and one or more control devices selected from supersonic wave sensor, digital temperature sensor, underwater mike, pressure sensor, vibrating motor, geomagnetic sensor and camera angle adjustor and several tying rings for the fishhook are formed; and a buoyancy regulating float connected to a point of said
15 multifunctional cable;

an external device part connected to the other end of said multifunctional cable, and comprised of a display panel which receives and displays various signals including image signals from said photographing part through said multifunctional cable, a controller communicating to the control devices through the multifunctional cable and controls them
20 by exchanging control signals through the multifunctional cable, and an electric power supplier which supplies power to the above photographing part, display panel and controller.

8. A fishing equipment with video system comprising:

25 a photographing part composed of a weight connected to one end of a multifunctional cable according to claim 1 through claim 6, having a built-in camera, one or more control devices selected from supersonic wave sensor, digital temperature sensor,

underwater mike, pressure sensor, vibrating motor, geomagnetic sensor and camera angle adjustor, several tying rings for the fishhook are formed, and a wireless radio sending/receiving float connected to said weight through said multifunctional cable and including a first radio sending/receiving circuit having an electric power supplier inside;
5 and

an external device part comprised of a second radio sending/receiving circuit exchanging signals with the first radio sending/receiving circuit; a display panel connected to the second radio sending/receiving circuit, and receives and displays various signals including image signals received by the second radio sending/receiving circuit from said
10 photographing part; a controller connected to the second radio sending/receiving circuit and controls the control devices by exchanging control signals through the second radio sending/receiving circuit; and an electric power supplier which supplies power to the second radio sending/receiving circuit, display panel and controller.

15 9. A fishing equipment with video system comprising:

a multifunctional cable according to claim 1 through claim 6;

a photographing part comprised of a weight connected to one end of said multifunctional cable, having a built-in camera and one or more control devices selected from supersonic wave sensor, digital temperature sensor, underwater mike, pressure sensor,
20 vibrating motor, geomagnetic sensor and camera angle adjustor, several tying rings for the fishhook are formed; and a buoyancy regulating float connected to a point of said multifunctional cable;

a wireless transceiver connected to the other end of said multifunctional cable, having a first radio sending/receiving circuit with an electric power supplier inside and
25 fixable to a point outside the water; and

an external device part comprised of a second radio sending/receiving circuit exchanging signals with the first radio sending/receiving circuit; a display panel connected

to the second radio sending/receiving circuit, and receives and displays various signals including image signals received by the second radio sending/receiving circuit from said photographing part; a controller connected to the second radio sending/receiving circuit, and controls the control devices by exchanging control signals through the second radio
5 sending/receiving circuit, and controls the display panel; and an electric power supplier which supplies power to the second radio sending/receiving circuit, display panel and controller.

10 10. The fishing equipment with video system according to claim 9, wherein the wireless transceiver is fixed at a point of grip part of the fishing pole.

11. The fishing equipment with video system according to claim 7 through claim 9, further comprising a fishing pole with an inlet hole and an outlet hole at both end parts of the fishing pole respectively, so that the multifunctional cable can pass through the fishing
15 pole.

12. The fishing equipment with video system according to claim 7 through claim 9, further comprising a connector which connects cut ends of the multifunctional cable between said weight of the photographing part and the float, so that the user can change the
20 weight of the photographing part easily.


13. The fishing equipment with video system according to claim 7 through claim 9, wherein the case of said weight of the photographing part is known lure shape, and a built-in camera is built inside the lure
25

14. The fishing equipment with video system according to claim 7 through claim 9, wherein the case of said weight of the photographing part is bisected case shape, which

has a hinge on one side and a fixing flange on the other side of the bisected case, so that said bisected case can be integrated and disintegrated using fixing bolts.

15. The fishing equipment with video system according to claim 7 through claim 9,
5 wherein the bottom part of said weight is filled with materials of high density, the middle part has a built-in camera and control devices, and the upper part has a void, so that said weight always stand stably under the water.

16. The fishing equipment with video system according to claim 7 through claim
10 9, further comprising certain length of flexible tube or a thin wire on the weight, so that the user can control the location of the fishhook and shooting angle of the camera.

17. The fishing equipment with video system according to claim 7 through claim 9,
wherein the camera angle adjustor is constructed by installing the  shaped fixture
15 driven by a motor in the weight so as to place each end of said fixture at each end of the weight case on the upper part of the weight, so that the camera angle is adjustable to any angle by driving said fixture through controlling the rotating direction of the motor by using the controller of the external device part.

20 18. The fishing equipment with video system according to claims 7 through claim 9, further comprising a underwater float at a point of the multifunctional cable connecting the weight and the buoyancy regulating float or the wireless radio sending/receiving float, and one or more supplementing weight hung to the ring attached to the bottom of the weight case, so as to prevent the weight from fluctuating under the water and help to
25 regulate the density of the weight.

19. The fishing equipment with video system according to claim 7 through claim 9, wherein the display panel, controller and electric power supplier of the external device part is constructed by adding a connector to connect with the end of the multifunctional cable or installing a radio sending/receiving circuit which exchange signals such as image signal with the wireless radio sending/receiving float of the photographing part or the wireless transceiver inside, to a known mobile phone with power supply unit, display unit, input unit, image storage unit and control unit.

20. An underwater image video system comprising:

a multifunctional cable according to Claims 1 through 6;

a photographing part comprised of a photographing device connected to one end of the multifunctional cable, having a built-in camera and one or more control device selected from supersonic wave sensor, digital temperature sensor, underwater mike, pressure sensor, geomagnetic sensor and camera angle adjustor inside; a diver's location indicating buoy connected to a point of said multifunctional cable; and a winding reel used to control the length of the multifunctional cable between the buoy and the photographing device according to the distance between the water surface and the diver;


an external device part connected to the other end of the above multifunctional cable and comprised of a display panel which receives and displays various signals including image signals from the photographing part through the multifunctional cable, a controller communicating with the control devices through the multifunctional cable and controls the control devices by exchanging control signals through the multifunctional cable, and an electric power supplier which supplies power to the above photographing part, display panel and controller.

21. An underwater image video system comprising:

a photographing part comprised of a photographing device connected to one end of the multifunctional cable according to Claims 1 through 6, having a built-in camera and one or more control devices selected from supersonic wave sensor, digital temperature sensor, underwater mike, pressure sensor, geomagnetic sensor and camera angle adjustor inside, a diver's location indicating buoy connected to the other end of the above multifunctional cable, having a first radio sending/receiving circuit inside, and a winding reel used to control the length of the multifunctional cable between the buoy and the photographing device according to the distance between the water surface and the diver;

an external device comprised of a second radio sending/receiving circuit exchanging signals with the first radio sending/receiving circuit; a display panel connected to the second radio sending/receiving circuit and receives and displays various signals including image signals received by the second radio sending/receiving circuit from the photographing part; a controller connected to the second radio sending/receiving circuit and controls the control devices by exchanging control signals through the second radio sending/receiving; and an electric power supplier which supplies power to the second radio sending/receiving circuit, display panel and controller.

22. The underwater image video system according to claim 20 or claim 21, further comprising a twin lens reflex on the exterior case of said photographing device, composed of a case of each end open and with at least one or more curves, a hinge installed on the curved part of the above case, and a reflector installed on the curved part to reflect the incident ray to a set degree.

23. An underwater image video system according to claim 20 or claim 21, wherein the camera angle adjustor is constructed by installing the  shaped fixtures driven by a motor in the photographing device so as to place each end of the fixture at each end of the photographing device case on the upper part of the photographing device, so that

the camera angle is adjustable to any angle by driving said fixture through controlling the rotating direction of the motor by using the controller of the external device part.

24. The underwater image video system according to claim 20 or claim 21,
5 wherein the display panel, controller and electric power supplier of the external device part is constructed by adding a connector to connect with the end of the multifunctional cable or installing a radio sending/receiving circuit which exchange signals such as image signal with the wireless radio sending/receiving circuit built in the buoy of the photographing part, to a known mobile phone with power supply unit, display unit, input unit, image storage
10 unit and control unit.

Abstract


Disclosed is a multifunctional cable, and fishing equipment and underwater image video system using the same.

The multi-functional cable according to the present invention comprising electric cords, a image signal cord and one or more control cords to transfer signals of sounds, supersonic waves, temperature information or control orders with individual inner coats, and exterior of these cords are molded or filled with flexible and durable molding resin or fibers, and the outer surface of the cable is covered with an abrasion resistant coat.


On the other hands, the fishing equipments with video system and underwater image video systems according to the present invention are using above mentioned multi-functional cables according to the present invention and the devices of the photographing part under the water and external device part out of the water are connected with each other using said multi-functional cable.

【DRAWINGS】


【FIG 1】




[FIG 2]




【FIG 3】



【FIG 4 a】




【FIG 4 b】




6/11


【FIG 5 a】




【FIG 5 b】




【FIG 6 a】




【FIG 6 b】




【FIG 7】




【FIG 8】



【FIG 9】



【FIG 10】



INTERNATIONAL SEARCH REPORT

International application No.

KR03/01103

A. CLASSIFICATION OF SUBJECT MATTER

IPC7 A01K 91/06, A01K 97/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7 A01K 91/06, A01K 97/00

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched
Korean Patents and applications for inventions since 1975,
Korean Utility models and applications for Utility models since 1975,

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)
KIPASS

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	KR 98-0076867 A (Cha, J.Y.) 16 November 1998	1-24
A	KR 99-0069961 A (Ma, J.W.) 06 August 1999	1-24
A	KR 00-0006799 A (Han, S.H.) 07 February 2000	1-24
A	KR 01-0092604 A (Lim, J.K.) 26 August 2001	1-24
A	KR 20-0217475 Y (Koa, Inc.) 15 March 2001	1-24

☐ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

27 OCTOBER 2003 (27.10.2003)

Date of mailing of the international search report

27 OCTOBER 2003 (27.10.2003)

Name and mailing address of the ISA/KR



Korean Intellectual Property Office
920 Dunsan-dong, Seo-gu, Daejeon 302-701,
Republic of Korea

Facsimile No. 82-42-472-7140

Authorized officer

LEE, Young Kee

Telephone No. 82-42-481-5628



INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No.

PC 3/01103

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
KR 98-0076867 A	16.11.1998	NONE	
KR 99-0069961 A	06.09.1999	NONE	
KR 00-0006799 A	07.02.2000	NONE	
KR 01-0092604 A	26.10.2001	NONE	
KR 20-0217475 Y	15.03.2001	NONE	



— *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.